

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
23 June 2005 (23.06.2005)

PCT

(10) International Publication Number
WO 2005/057770 A1

- (51) International Patent Classification⁷: **H02M 7/00**
- (21) International Application Number:
PCT/IB2004/003920
- (22) International Filing Date:
30 November 2004 (30.11.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003-410445 9 December 2003 (09.12.2003) JP
- (71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP]**; 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **NAKAYAMA, Hiroshi [JP/JP]**; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: POWER CONVERTER AND VEHICLE EQUIPPED WITH POWER CONVERTER



(57) Abstract: A power source (120) supplies an input voltage (V1). A voltage conversion circuit (130) converts the input voltage (V1) from the power source (120) into an operating voltage (V2) to be used to drive an electric load (150). A detection circuit (170) measures an insulation resistance value (R) on the output side of the voltage conversion circuit (130). A control circuit (160) controls a voltage conversion ratio (K ($K=V2/V1$)) in the voltage conversion circuit (130), which is expressed as a ratio of the operating voltage (V2) to the input voltage (V1), in accordance with the insulation resistance value (R) detected by the detection circuit (170). The control circuit (160) sets the voltage conversion ratio (K) such that the operating voltage (V2) becomes lower at the time of degradation of an insulation resistance than at the time of normal operation thereof.